

Maytapi - WhatsApp API Documentation

Overview

This API deals with a chatting platform based on WhatsApp. The user can send and receive text and media messages through WhatsApp in private chats with the endpoints that are created for the user. Moreover, the current status and the screen of the session can be retrieved using these endpoints. With the account specific endpoints, user can get the product or registered phones information, edit and remove these.

Example Projects:

[Maytapi WhatsApp Api NodeJS Example](<https://github.com/maytapi-com/whatsapp-api-nodejs-example>)

[Maytapi WhatsApp Api NodeJS Dialogflow Example](<https://github.com/maytapi-com/whatsapp-api-nodejs-dialogflow-example>)

[Maytapi WhatsApp Api Python Example](<https://github.com/maytapi-com/whatsapp-api-python-example>)

[Maytapi WhatsApp Api Python Dialogflow Example](<https://github.com/maytapi-com/whatsapp-api-python-dialogflow-example>)

You need to send 'x-maytapi-key': 'YOUR_TOKEN' header with every request.

You can find your **product_id** and **token** at <https://console.maytapi.com/settings/token>

You can find **message examples** in /sendMessage documentation section [Screenshot](<https://maytapi.com/images/sendmessage.png>) | Feature | Status | Description |
|:-----|:-----|:-----| | Receive message | ☐ | You need to set your webhook with /setWebhook endpoint. | | Receive media | ☐ | Image, Video, Docs/File, Audio, Location, vCard supported. | | Send Text Message | ☐ | Send message works with queue. Message id and success response states that message added to sending queue.
If your messages isn't send check your instance status for connection/login problems.
You can also check /logs endpoint or [Developer Logs Page](<https://console.maytapi.com/developers/logs>) for error messages if you are using wrong format you can find the error in here.
 You can also check your queue status in [Developer Webhook Page](<https://console.maytapi.com/developers/webhook>) or with /{phone_id}/queue endpoint. / | | Send Media | ☐ | Image, Audio(ogg-file in opus codec), Video, Docs(pdf,docx,etc.) supported. | | Send vCard | ☐ | You can find the example in /sendMessage → Examples → vCard Message | | Send Contact | ☐ | You can find the example in /sendMessage → Examples → Contact Message | | Send Location | ☐ | You can find the example in /sendMessage → Examples → Location Message | | Send Product | ☐ | You can find the example in /sendMessage → Examples → Product Message (**Beta**)
You need to create products from WhatsApp Business

Phone App.
You can find Product Ids from new **/catalog** endpoint. | | Forward Messages | | You can find the example in /sendMessage → Examples → Forward Message | | Reply to Messages | | You can find the example in /sendMessage → Examples → Reply Message | | Delete Messages | | You can find the example in /sendMessage → Examples → Delete Message | | Reaction Message | | You can find the example in /sendMessage → Examples → Reaction Message | | Edit Message | | You can find the example in /sendMessage → Examples → Edit Message | | Create Groups | | You can find the example in **/phone_id/createGroup** | | Get groups | | You can find the example in **/phone_id/getGroups** | Mention Message for Groups | | You can find the example in /sendMessage → Examples → Group Mention Message | | Leave Group | | You can find the example in **/leaveGroup** | | New Spam Filter | | We added a new spam/dupe filter for recurring messages in the same conversation. In a conversation, the last 3 unique messages can't be sent more than 3 times.
This feature is to ignore spam messages sent to the same user. Sending same message to different users is not filtered.
You can also ignore the filter by adding **"skip_filter":true** to messages. You can find an example for this in /sendMessage examples section. | | Listen to Read Receipts | | You need to enable this with **/setAckPreference** endpoint. | | Webhook examples. | | You can find webhook examples in **Callbacks** tab of **/setWebhook** endpoint definition. | | WhatsApp Channel Example | | You can find **Channel Chat Operations** | | WhatsApp Story Example | | You can find **Story Operations (Beta)**

[Terms Of Service](#)

Tags

Account Information Retrieval::Session Information Getters::Message Sending Operations::Message Info::Business Catalog (Beta)::Group Chat Operations::Channel Chat Operations::Story Operations (Beta)::Queue Operations::Session Controlling Operations
 == Security

Type	Name	Scopes
oauth2	ApiKeyAuth	x-maytapi-key

Paths

GET /product

Returns the information of the product with the given product id.

Responses

Code	Description	Links
200	Content application/json	No Links

GET /listPhones

Returns information of all the phones registered to the given product.

Responses

Code	Description	Links
200	<i>Content</i> application/json	No Links

GET /queues

Returns information of all the phones registered to the given product with queue information.

Responses

Code	Description	Links									
200	<i>Content</i> application/json <i>Properties</i> <table><tr><th>Name</th><th>Description</th><th>Schema</th></tr><tr><td>success <i>optional</i></td><td></td><td>boolean</td></tr><tr><td>queues <i>optional</i></td><td></td><td>< [components_schemas_queue-phone] > array</td></tr></table>	Name	Description	Schema	success <i>optional</i>		boolean	queues <i>optional</i>		< [components_schemas_queue-phone] > array	No Links
Name	Description	Schema									
success <i>optional</i>		boolean									
queues <i>optional</i>		< [components_schemas_queue-phone] > array									

POST /setWebhook

Sets a webhook address for the selected product. Webhook is used for delivering the incoming messages and acknowledge notifications of sent messages to the user. The notification formats that reaches to the webhook are as follows:

Responses

Code	Description	Links
200	Returns the information of updated selected product. <i>Content</i> application/json	No Links

POST /addPhone

Adds a new phone to the product.

Responses

Code	Description	Links
200	<i>Content</i> application/json	No Links

POST /setAckPreference

Sets the option for getting the acknowledge messages from the webhook to true or false.

Responses

Code	Description	Links
200	Returns the information of updated selected product. <i>Content</i> application/json	No Links

GET /logs

Returns logs of all the phones.

Responses

Code	Description	Links						
200	<i>Content</i> application/json <i>Properties</i> <table> <tr> <th>Name</th><th>Description</th><th>Schema</th></tr> <tr> <td>success <i>optional</i></td><td></td><td>boolean</td></tr> </table> <.<!Name <.<!Description <.<!Schema <.<!count <i>optional</i> <.<! <.<!string <.<!list <i>optional</i> <.<! <.<![_components_schemas_logslist] object	Name	Description	Schema	success <i>optional</i>		boolean	No Links
Name	Description	Schema						
success <i>optional</i>		boolean						

GET /{phone_id}/screen

Returns the status of the current session.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	_components_schemas_phone-id

Responses

Code	Description	Links
200	Returns the screenshot of the screen in the current session.	No Links

GET /{phone_id}/status

Returns the screenshot of the screen in the current session.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	<i>Content</i> application/json	No Links

GET /{phone_id}/queue

Returns the queue info of the phone.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links									
200	Returns the queue info of the phone. Content application/json Properties <table><thead><tr><th>Name</th><th>Description</th><th>Schema</th></tr></thead><tbody><tr><td>success</td><td></td><td>boolean</td></tr><tr><td>optional</td><td></td><td></td></tr></tbody></table> <.<!Name <.<!Description <.<!Schema <.<!sending optional <.<! <.<!integer object	Name	Description	Schema	success		boolean	optional			No Links
Name	Description	Schema									
success		boolean									
optional											

GET /{phone_id}/purgeQueue

Clears phone's send message queue.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas _phone-id]

Responses

Code	Description	Links						
200	Clears phone's send message queue. <i>Content</i> application/json <i>Properties</i> <table><tr><th>Name</th><th>Description</th><th>Schema</th></tr><tr><td>success <i>optional</i></td><td></td><td>boolean</td></tr></table>	Name	Description	Schema	success <i>optional</i>		boolean	No Links
Name	Description	Schema						
success <i>optional</i>		boolean						

GET /{phone_id}/qrCode

Returns the qrCode in the current session if there is one.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas _phone-id]

Responses

Code	Description	Links
200	Returns the screenshot of the qr code in the current session.	No Links

GET /{phone_id}/contacts

Returns the contacts in the current whatsapp instance.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links									
200	Returns the contacts in the current whatsapp instance. <i>Content</i> application/json <i>Properties</i> <table> <tr> <th>Name</th><th>Description</th><th>Schema</th></tr> <tr> <td>success <i>optional</i></td><td></td><td>boolean</td></tr> <tr> <td>data <i>optional</i></td><td></td><td>< object > array</td></tr> </table>	Name	Description	Schema	success <i>optional</i>		boolean	data <i>optional</i>		< object > array	No Links
Name	Description	Schema									
success <i>optional</i>		boolean									
data <i>optional</i>		< object > array									

GET /{phone_id}/contact/:cid

Returns the information of the number you specified in Whatsapp

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links									
200	Returns the information of the number you specified in Whatsapp <i>Content</i> application/json <i>Properties</i> <table> <tr> <th>Name</th><th>Description</th><th>Schema</th></tr> <tr> <td>success <i>optional</i></td><td></td><td>boolean</td></tr> <tr> <td>data <i>optional</i></td><td></td><td>< object > array</td></tr> </table>	Name	Description	Schema	success <i>optional</i>		boolean	data <i>optional</i>		< object > array	No Links
Name	Description	Schema									
success <i>optional</i>		boolean									
data <i>optional</i>		< object > array									

GET /{phone_id}/redeploy

Redeploys docker instance of your phone. If your phone having any unexpected problems you can use this endpoint to reboot the instance.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas _phone-id]

Responses

Code	Description	Links									
200	<i>Content</i> application/json <i>Properties</i> <table><tr><th>Name</th><th>Description</th><th>Schema</th></tr><tr><td>success <i>optional</i></td><td></td><td>boolean</td></tr><tr><td>message <i>optional</i></td><td></td><td>string</td></tr></table>	Name	Description	Schema	success <i>optional</i>		boolean	message <i>optional</i>		string	No Links
Name	Description	Schema									
success <i>optional</i>		boolean									
message <i>optional</i>		string									

GET /{phone_id}/factoryreset

Factory resets everything about phone instance to a new created instance state. This is a replacement for delete/create a new phone.

Your phone instances can't be deleted anymore. This is implemented beacuse some of our customers were loosing their phone instance when their subscription(or trial) suspended. With the new system your phones would only set to disabled state and after you fix your subscription you can re-enable your phones either making a request(screen etc.) to instance or from our control panel.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas _phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

GET /{phone_id}/logout

Logouts the number from the current session and converts the screen to qr-code screen.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

GET /{phone_id}/config

Get phone specifig config for webhook and ack_delivery. If empty product webhook config would be used for delivery.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

POST /{phone_id}/config

Set phone specifig config for webhook and ack_delivery. If empty product webhook config would be used for delivery.

With this api you can define webhook for individual phones.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	<i>Content</i> application/json	No Links

GET /{phone_id}/connectWithPhoneNumber

Connect with the phone number for your phone with the Get operation

Parameters

Type	Name	Description	Schema
query	number <i>required</i>	The phone number you will use to log in to the instance.	string
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links									
200	Get your code to connect to your physical phone Link with phone number instead <i>Content</i> application/json <i>Properties</i> <table> <tr> <th>Name</th><th>Description</th><th>Schema</th></tr> <tr> <td>success <i>optional</i></td><td>Default: true</td><td>boolean</td></tr> <tr> <td>connectionResult <i>optional</i></td><td></td><td>string</td></tr> </table>	Name	Description	Schema	success <i>optional</i>	Default: true	boolean	connectionResult <i>optional</i>		string	No Links
Name	Description	Schema									
success <i>optional</i>	Default: true	boolean									
connectionResult <i>optional</i>		string									

POST /{phone_id}/connectWithPhoneNumber

Connect with the phone number for your phone with the post operation

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links									
200	<i>Content</i> application/json <i>Properties</i> <table> <tr> <th>Name</th><th>Description</th><th>Schema</th></tr> <tr> <td>success <i>optional</i></td><td>Default: true</td><td>boolean</td></tr> <tr> <td>connectionResult <i>optional</i></td><td></td><td>string</td></tr> </table>	Name	Description	Schema	success <i>optional</i>	Default: true	boolean	connectionResult <i>optional</i>		string	No Links
Name	Description	Schema									
success <i>optional</i>	Default: true	boolean									
connectionResult <i>optional</i>		string									

***GET* /{phone_id}/delete DEPRECATED please use /factoryreset**

[DEPRECATED please use /factoryreset] Deletes the phone and closes the session of that number.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	<i>Content</i> application/json	No Links

***GET* /{phone_id}/restart DEPRECATED please use /redploy**

[DEPRECATED please use /redploy] Restarts the session by refreshing the page.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

GET /{phone_id}/backup DEPRECATED Multi-Device doesn't support this feature.

[DEPRECATED Multi-Device doesn't support this feature] Backups the material needed for opening the same chat screen for the current phone number. This call is useful when the session and also the status of the session is active. The response information can be used to open the chat screen with the POST restore call. If logout is called after getting the backup information, the data obtained from there will not be valid anymore.

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

POST /{phone_id}/restore DEPRECATED Multi-Device doesn't support this feature.

[DEPRECATED Multi-Device doesn't support this feature] Reloads the current session based on the reload data (can be obtained from **POST backup**).

Parameters

Type	Name	Description	Schema
path	phone_id <i>required</i>	ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling GET listPhones .	[_components_schemas_phone-id]

Responses

Code	Description	Links
200	Content application/json	No Links

POST /{phone_id}/sendMessage

Used for sending message to a chat. A text, image, video, sound and document can be sent.

This endpoint adds messages to your phone's sending queue. If your messages not delivering to phones please check your instance logs, queue endpoint or connection (/screen).

Curl example: (You need to change product_id, phone_id and token[x-maytapi-key] with your product's values...)

```
curl -X POST \
'https://api.maytapi.com/api/dc01968f-####-####-####-7cfcf51aa423/12/sendMessage' \
-H 'Content-Type: application/json' \
-H 'x-maytapi-key: b267697c-####-####-####-2435e812efc1' \
-d '{
  "message": "http://placeholder.it/180",
  "text": "",
  "to_number": "+905301111111",
  "type": "media"
}'
```

```
.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|**path**
```

```
<.<|**phone_id** +
__required__
```

<.<|ID of the phone registered to the product, assigned by the database automatically. Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
 .Responses
 [%header,caption=,cols=".^2a,.^14a,.^4a"]
 |===
 <.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the id of the chat and the id of the message. You can use message id to track acknowledgement status.

.Content
 application/json::

<.<|No Links

|===

=== __GET__ `/{phone\_id}/catalog`
 Returns catalog products info of the business profile. You only need productId to send products to users.

.Parameters
 [%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
 |===
 <.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns catalog products info of the business profile

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<!Description

<.<!Schema

<.<!success
__optional__

<.<!
<.<!boolean

<.<!data
__optional__

<.<!
<.<!
<<_components_schemas_product-data>>
> array

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/createGroup`
Sets the option for getting the acknowledge messages from the webhook to true or false.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the information of updated selected product.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<!Schema

<.<!success
__optional__

<.<!
<.<!boolean

<.<!data
__optional__

<.<!
<.<!!<<_components_schemas_groupdata>>

!===

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getGroups`
Get conversations list.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**query**

<.<|**sort** +
__optional__

<.<|Sort groups by id.

<.<|boolean

<.<|**query**

<.<|**invite** +
__optional__

<.<|Include invite links for groups. (Max response limit:50)

<.<|boolean

<.<|**query**

<.<|**page** +
__optional__

<.<|Paging for groups. We suggest to use with **sort** option.

<.<|integer

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

<.<|**query**

<.<|**full** +
__optional__

<.<|Load participants for old conversations. (Max response limit:100)

<.<|boolean

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the information of updated selected product.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<!Schema

<.<!success
__optional__

<.<!
<.<!boolean

<.<!count
__optional__

<.<!
<.<!integer

<.<!total
__optional__

<.<!
<.<!integer

<.<!limit
__optional__

<.<!
<.<!integer

<.<!page
__optional__

<.<!
<.<!integer

<.<!data

__optional__

```
<.<!  
<.<!  
<<_components_schemas_groupdata>>  
> array
```

!===

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getGroups/{conversation\_id}`
Get a conversation info.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**conversation_id** +
__required__

<.<|Load conversations info.

<.<|string

<.<|**query**

<.<|**invite** +
__optional__

<.<|Generate invite link for group.

<.<|boolean

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the information of updated selected product.

.Content
application/json::
+

```
.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<!Name
```

```
<.<!Description
```

```
<.<!Schema
```

```
<.<!success
__optional__
```

```
<.<!
<.<!boolean
```

```
<.<!data
__optional__
```

```
<.<!
<.<!!<<_components_schemas_groupdata>>
```

```
!===
```

```
<.<|No Links
```

```
|===
```

```
=== __POST__ `/{phone_id}/setProfileImage`
Change profile picture of a group conversation or yourself.
```

To change profile picture of yourself you need to leave the conversation_id blank.

You need to use square images for better view. We suggest 512x512 images.

```
.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
```

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the success information about the action.

.Content
application/json::
+

```
.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success
__optional__
```

```
<.<|
<.<|boolean
```

```
!===
```

```
<.<|No Links
```

```
|===
```

```
=== __POST__ `/{phone_id}/group/config`
Change config of a group conversation.
```

To learn conversation_id you can use /getGroups endpoint.

You can change who can edit group info(edit), can send message(send) and disappearing messages enabled(disappear).

For edit and send config you can use values "admins" or "all".

Disappear only accepts true/false values.

Config values are optional. If you want to only change a config you should only use that config's key in request body.

```
.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type
```

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the success information about the action.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]

```

!===
<.<!Name

<.<!Description

<.<!Schema

<.<!success
__optional__

<.<!
<.<!boolean

<.<!data
__optional__

<.<!.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<!Name

<.<!Description

<.<!Schema

<.<!edit
__optional__

<.<!
<.<!enum (admins,all)

<.<!send
__optional__

<.<!

```

```
<.<!enum (admins,all)
```

```
<.<!disappear  
__optional__
```

```
<.<!--Default--: false
```

```
<.<!boolean
```

```
<.<!membersCanAddMembers  
__optional__
```

```
<.<!--Default--: true
```

```
<.<!boolean
```

```
<.<!approveNewMembers  
__optional__
```

```
<.<!--Default--: true
```

```
<.<!boolean
```

```
<.<!name  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!description  
__optional__
```

```
<.<!
```

<.<!string

!===

<.<!object

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/group/add`
Add a participant to a group conversation.

To learn conversation_id you can use /getGroups endpoint.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

```
<.<|<<_components_schemas_phone-id>>
```

```
|===  
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===  
<.<|Code
```

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|Returns the success information about the action.
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
!===
```

<.<|No Links

|===

=== __POST__ `/{phone\_id}/group/remove`

Remove a participant from a group conversation.

To learn conversation_id you can use /getGroups endpoint.

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +

__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===

.Responses

[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===

<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the success information about the action.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/group/promote`
Promote a participant in a group conversation.

To learn conversation_id you can use /getGroups endpoint.

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===

.Responses

[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===

<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the success information about the action.

.Content

application/json::

+

.Properties

[%header,caption=,cols=".^4a,.^16a,.^4a"]

!===

<.<!Name

<.<!Description

<.<!Schema

<.<!success

__optional__

<.<!

<.<!boolean

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/group/demote`

Demote a participant in a group conversation.

To learn conversation_id you can use /getGroups endpoint.

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the success information about the action.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<!Schema

<.<!success
__optional__

<.<!
<.<!boolean

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/leaveGroup`
You can leave the group you want with the help of this endpoint.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

```
<.<|<<_components_schemas_phone-id>>
```

```
|===  
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===  
<.<|Code
```

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|Returns the success information about the action.
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|data
```

__optional__

<.<!

<.<!boolean

!===

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getConversations/:cid`

You can find out who the conversation is between, your messages, and your phone.

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +

__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

```

|===
Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|The returned result is as shown in the example below.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

<.<|
<.<|< <<_components_schemas_getconversationsdata>>

```

```
> array
```

```
!===
```

```
<.<|No Links
```

```
|===
```

```
=== __POST__ `/{phone_id}/createChannel`  
Channel creation feature.
```

```
.Parameters  
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]  
|===  
<.<|Type
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|**path**
```

```
<.<|**phone_id** +  
__required__
```

```
<.<|ID of the phone registered to the product, assigned by the database automatically.  
Can be obtained by calling ***GET listPhones***.
```

```
<.<|<<_components_schemas_phone-id>>
```

```
|===
```

```
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===
```

```

<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Return the information of the new channel created.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

<.<|
<.<|<<_components_schemas_createchannel>>

!===

```

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getChannels`
Get all channels list

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**query**

<.<|**invite** +
__optional__

<.<|Generate invite link for channel.

<.<|boolean

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

```
<.<|<<_components_schemas_phone-id>>
```

```
|===  
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===  
<.<|Code
```

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|Get all channels list
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|data
```

__optional__

```
<.<!  
<.<!< <<_components_schemas_channeldata>>  
  > array
```

!===

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getChannels/{conversation\_id}`
Get a channel info

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**query**

<.<|**invite** +
__optional__

<.<|Generate invite link for group.

<.<|boolean

```
<.<|**path**
```

```
<.<|**phone_id** +  
__required__
```

```
<.<|ID of the phone registered to the product, assigned by the database automatically.  
Can be obtained by calling ***GET listPhones***.
```

```
<.<|<<_components_schemas_phone-id>>
```

```
|===  
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===  
<.<|Code
```

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|Get a channel info
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```

<.<!success
__optional__

<.<!
<.<!boolean

<.<!data
__optional__

<.<!
<.<|< <<_components_schemas_channeldata>>
  > array

!===

<.<|No Links

|===

=== __POST__ `/{phone_id}/channel/deleteChannel`
Channel delete feature.

.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +

```

__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Return the status of Channel Delete operation

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

```
<.<!  
<.<!boolean
```

```
<.<!data  
__optional__
```

```
<.<!  
<.<!boolean
```

```
!===
```

```
<.<|No Links
```

```
|===
```

```
=== __POST__ `/{phone_id}/channel/config`  
You can change your channel name, description and image.
```

```
.Parameters  
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]  
|===  
<.<|Type
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|**path**
```

```
<.<|**phone_id** +  
__required__
```

```
<.<|ID of the phone registered to the product, assigned by the database automatically.  
Can be obtained by calling ***GET listPhones***.
```

```
<.<|<<_components_schemas_phone-id>>
```

```
|===  
.Responses  
[%header,caption=,cols=".^2a,.^14a,.^4a"]  
|===  
<.<|Code
```

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|Returns the information of updated selected product.
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<!data
__optional__
```

```
<.<!
<.<!boolean
```

```
!===
```

```
<.<|No Links
```

```
|===
```

```
=== __POST__ `/{phone_id}/channel/inviteCode`
Channel invite code feature.
```

```
.Parameters
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
|===
<.<|Type
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|**path**
```

```
<.<|**phone_id** +
__required__
```

```
<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.
```

```
<.<|<<_components_schemas_phone-id>>
```

```

|===
.Responses
[%header,caption=,cols=".^2a,.^14a,.^4a"]
|===
<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Returns the information of updated selected product.

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

<.<|

```

<.<|string

!===

<.<|No Links

|===

=== __GET__ `/{phone\_id}/getStories`

Allows you to get information about the story you share

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +

__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling ***GET listPhones***.

<.<|<<_components_schemas_phone-id>>

|===

.Responses

[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===

```

<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|Allows you to get information about the story you share

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

<.<|
<.<|< <<_components_schemas_statusdata>>
> array

```

!===

<.<|No Links

|===

=== __POST__ `/{phone\_id}/shareStory`

You can share media (image, video) your stories. This feature is currently in Beta, you may experience some media items not being shared.

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +
__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling **GET listPhones**.

<.<|<<_components_schemas_phone-id>>

|===

.Responses

[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===

<.<|Code

```
<.<|Description
```

```
<.<|Links
```

```
<.<|200
```

```
<.<|We give you back the ID of the text Story you shared.
```

```
.Content  
application/json::  
+
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|data  
__optional__
```

```
<.<|  
<.<|string
```

```
!===
```

```
<.<|No Links
```

|===

=== __GET__ `/{phone\_id}/contactsStories`

You can access the stories of people in your contact list here

.Parameters

[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]

|===

<.<|Type

<.<|Name

<.<|Description

<.<|Schema

<.<|**path**

<.<|**phone_id** +

__required__

<.<|ID of the phone registered to the product, assigned by the database automatically.
Can be obtained by calling **GET listPhones**.

<.<|<<_components_schemas_phone-id>>

|===

.Responses

[%header,caption=,cols=".^2a,.^14a,.^4a"]

|===

<.<|Code

<.<|Description

<.<|Links

<.<|200

<.<|You can access the stories of people in your contact list here

.Content
application/json::
+

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|chatId

__optional__

<.<!
<.<!string

<.<!storieContent
__optional__

<.<!
<.<!< string > array

!===

<.<!object

!===

<.<|No Links

|===

[[_components]]
== Components
[[_components_schemas]]
=== Schemas
[[_components_schemas_status]]
==== Status

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

```
<.<|success
__optional__
```

```
<.<|
<.<|boolean
```

```
<.<|status
__optional__
```

```
<.<|
<.<|<<_components_schemas_substatus>>
```

```
|===
[[_components_schemas_phone_config]]
==== phone_config
```

```
.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success
__optional__
```

```
<.<|**Default**: true
```

```
<.<|boolean
```

```
<.<|status
__optional__
```

```

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<!Name

<.<!Description

<.<!Schema

<.<!webhook
__optional__

<.<!
<.<!<<_components_schemas_webhook-url>>

<.<!ack_delivery
__optional__

<.<!**Default**: false

<.<!boolean

!===

<.<|object

|===
[[_components_schemas_backupdata]]
==== backupData

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|WABrowserId  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|debugCursor  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|whatsapp-mutex  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|(other_keys)  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_justsuccess]]  
==== justSuccess
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
|===  
[[_components_schemas_addphonebody]]  
==== addPhoneBody
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|number  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_productdata]]  
==== productData
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|pid  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_product-id>>
```

```
<.<|webhook  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_webhook-url>>
```

```
<.<|ack_delivery  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|phone_limit  
__optional__
```

```
<.<|  
<.<|integer
```

```
|===  
[[_components_schemas_phonelist]]  
==== phoneList
```

```
[[_components_schemas_logincoming]]
```

```

==== logIncoming

[[_components_schemas_logoutgoing]]
==== logOutgoing

[[_components_schemas_logobj]]
==== logObj

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|id
__optional__

<.<|
<.<|integer

<.<|pid
__optional__

<.<|
<.<|<<_components_schemas_product-id>>

<.<|phone
__optional__

<.<|
<.<|<<_components_schemas_phone-id>>

<.<|created_at
__optional__

```

```
<.<|  
<.<|string
```

```
<.<|updated_at  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|type  
__optional__
```

```
<.<|  
<.<|enum (incoming,outgoing,error)
```

```
<.<|data  
__optional__
```

```
<.<|  
<.<|object
```

```
|===  
[[_components_schemas_logslist]]  
==== logslist
```

```
[[_components_schemas_incomingmessageuserdata]]  
==== incomingMessageUserData
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|id
__optional__
```

```
<.<|
<.<|<<_components_schemas_conversation-id>>
```

```
<.<|name
__optional__
```

```
<.<|
<.<|string
```

```
<.<|phone
__optional__
```

```
<.<|
<.<|string
```

```
<.<|image
__optional__
```

```
<.<|
<.<|string
```

```
|===
[[_components_schemas_webhook-ack-data]]
==== webhook-ack-data
```

```
.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name
```

```
<.<|Description
```

```

<.<|Schema

<.<|ackType
__optional__

<.<|
<.<|enum (delivered,reached,seen,played,deleted)

<.<|ackCode
__optional__

<.<|
<.<|enum (1,2,3,4,5)

<.<|chatId
__optional__

<.<|
<.<|<<_components_schemas_conversation-id>>

<.<|msgId
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|time
__optional__

<.<|
<.<|integer

|===
[[_components_schemas_webhook-ack-body]]

```

```

==== webhook-ack-body

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: ack

<.<|string

<.<|product_id
__optional__

<.<|
<.<|<<_components_schemas_product-id>>

<.<|data
__optional__

<.<|
<.<|< <<_components_schemas_webhook-ack-data>>
> array

|===
[[_components_schemas_webhook-live-body]]
==== webhook-live-body

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]

```

```

|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: live_event

<.<|string

<.<|product_id
__optional__

<.<|
<.<|<<_components_schemas_product-id>>

<.<|phone_id
__optional__

<.<|
<.<|<<_components_schemas_phone-id>>

<.<|conversation
__optional__

<.<|
<.<|<<_components_schemas_conversation-id>>

<.<|data
__optional__

```

```

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema

<.<|event
__optional__

<.<|
<.<|enum (taken_by_agent,closed,released_by_agent)

!===

<.<|object

|===
[[_components_schemas_webhook-status-body]]
==== webhook-status-body

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

```

```

<.<|**Default**: status

<.<|string

<.<|pid
__optional__

<.<|
<.<|<<_components_schemas_product-id>>

<.<|phone_id
__optional__

<.<|
<.<|<<_components_schemas_phone-id>>

<.<|status
__optional__

<.<|
<.<|<<_components_schemas_status-enum>>

|===
[[_components_schemas_status-enum]]
==== status-enum

[[_components_schemas_substatus]]
==== subStatus

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

```

```
<.<|loggedIn  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|isQr  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|loading  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|connRetry  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|message  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_incomingmessagetype]]  
==== incomingMessageType
```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|product_id
__optional__

<.<|
<.<|<<_components_schemas_product-id>>

<.<|phone_id
__optional__

<.<|
<.<|<<_components_schemas_phone-id>>

<.<|message
__optional__

<.<|
<.<|<<_components_schemas_message-data>>

<.<|user
__optional__

<.<|
<.<|<<_components_schemas_incomingmessageuserdata>>

<.<|conversation

```

__optional__

<.<|
<.<|<<_components_schemas_conversation-id>>

<.<|receiver
__optional__

<.<|
<.<|string

<.<|timestamp
__optional__

<.<|
<.<|integer

<.<|type
__optional__

<.<|
<.<|string

<.<|reply
__optional__

<.<|Reply url for ease of use.

<.<|string

<.<|quoted
__optional__

<.<|

```
<.<|<<_components_schemas_message-quoted-data>>
```

```
|===  
[[_components_schemas_phoneobjwithpid]]  
==== phoneObjWithPid  
  
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|id  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|pid  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_product-id>>
```

```
<.<|number  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_ackset]]  
==== ackSet
```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|ack_delivery
__optional__

<.<|
<.<|boolean

|===
[[_components_schemas_backupsuccess]]
==== backupSuccess

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

<.<|data
__optional__

```

```
<.<|  
<.<|<<_components_schemas_backupdata>>
```

```
|===  
[[_components_schemas_deletesuccess]]  
==== deleteSuccess
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|success  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|type  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|pid  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_product-id>>
```

```

<.<|phone_id
__optional__

<.<|
<.<|string

|===
[[_components_schemas_sendmessageresponsedata]]
==== sendMessageResponseData

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|chatId
__optional__

<.<|
<.<|string

<.<|msgId
__optional__

<.<|
<.<|string

|===
[[_components_schemas_sendmessagebody]]
==== sendMessageBody

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===

```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|to_number  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|message  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|type  
__optional__
```

```
<.<|  
<.<|enum (text,media)
```

```
|===  
[[_components_schemas_phoneobj]]  
==== phoneObj
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|id
__optional__
```

```
<.<|
<.<|integer
```

```
<.<|number
__optional__
```

```
<.<|
<.<|string
```

```
<.<|status
__optional__
```

```
<.<|
<.<|<<_components_schemas_status-enum>>
```

```
|===
[[_components_schemas_queue-phone]]
==== queue-phone
```

```
.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|id
__optional__
```

```

<.<|
<.<|integer

<.<|status
__optional__

<.<|
<.<|<<_components_schemas_status-enum>>

<.<|queue
__optional__

<.<|
<.<|integer

|===
[[_components_schemas_webhook-url]]
==== webhook-url

[[_components_schemas_sendmessageresponse]]
==== sendMessageResponse

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|success
__optional__

<.<|
<.<|boolean

```

```

<.<|data
__optional__

<.<|
<.<|<<_components_schemas_sendmessageresponsedata>>

|===
[[_components_schemas_groupdata]]
==== groupData

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|id
__optional__

<.<|
<.<|string

<.<|name
__optional__

<.<|
<.<|string

<.<|participants
__optional__

<.<|
<.<|< string > array

```

```
<.<|admins  
__optional__
```

```
<.<|  
<.<|< string > array
```

```
<.<|config  
__optional__
```

```
<.<|.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
!===  
<.<!Name
```

```
<.<!Description
```

```
<.<!Schema
```

```
<.<!edit  
__optional__
```

```
<.<!  
<.<!enum (admins,all)
```

```
<.<!send  
__optional__
```

```
<.<!  
<.<!enum (admins,all)
```

```
<.<!disappear  
__optional__
```

```

<.<!
<.<!boolean

<.<!membersCanAddMembers
__optional__

<.<!
<.<!boolean

<.<!approveNewMembers
__optional__

<.<!
<.<!boolean

!===

<.<|object

|===
[[_components_schemas_statusdata]]
==== statusData

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|id
__optional__

<.<|

```

```

<.<|string

<.<|storieContent
__optional__

<.<|
<.<|string

<.<|viewers
__optional__

<.<|
<.<|< array > array

|===
[[_components_schemas_getconversationsdata]]
==== getConversationsData

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|users
__optional__

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<!Name

<.<!Description

```

```
<.<!Schema
```

```
<.<!id  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!name  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!phone  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!image  
__optional__
```

```
<.<!  
<.<!string
```

```
!===
```

```
<.<|object
```

```
<.<|messages  
__optional__
```

```

<.<|
<.<|< <<_components_schemas_messageresponse>>
  > array

<.<|me
__optional__

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<!Name

<.<!Description

<.<!Schema

<.<!id
__optional__

<.<!
<.<!integer

<.<!phone
__optional__

<.<!
<.<!string

!===

<.<|object

|===
[[_components_schemas_messageresponse]]
==== messageResponse

```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|timestamp
__optional__

<.<|
<.<|string

<.<|uid
__optional__

<.<|
<.<|string

<.<|fromMe
__optional__

<.<|
<.<|boolean

<.<|message
__optional__

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

```

```
<.<!Schema
```

```
<.<!type  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!text  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!id  
__optional__
```

```
<.<!  
<.<!string
```

```
<.<!_serialized  
__optional__
```

```
<.<!  
<.<!string
```

```
!===
```

```
<.<|object
```

```
|===  
[[_components_schemas_channeldata]]  
==== channelData
```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema


<.<|id
__optional__

<.<|.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
!===
<.<|Name

<.<|Description

<.<|Schema


<.<|server
__optional__

<.<|
<.<|string


<.<|user
__optional__

<.<|
<.<|string


<.<|_serialized
__optional__

```

```
<.<!  
<.<|string
```

```
!===
```

```
<.<|object
```

```
<.<|channelName  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|owner  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|subscribeCount  
__optional__
```

```
<.<|  
<.<|integer
```

```
<.<|inviteLink  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_createchannel]]
```

```

==== createChannel

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|id
__optional__

<.<|
<.<|channelId

<.<|name
__optional__

<.<|
<.<|channelName

|===
[[_components_schemas_product-id]]
==== product-id

[[_components_schemas_phone-id]]
==== phone-id

[[_components_schemas_conversation-id]]
==== conversation-id

[[_components_schemas_message-id]]
==== message-id

[[_components_schemas_message-quoted-data]]
==== message-quoted-data

__nullable__

```

```

[[_components_schemas_message-data]]
==== message-data

[[_components_schemas_text-message]]
==== text-message

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: text

<.<|string

<.<|id
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|text
__optional__

<.<|
<.<|string

<.<|fromMe
__optional__

```

```

<.<|
<.<|boolean

|===
[[_components_schemas_mention-message]]
==== mention-message

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: text

<.<|string

<.<|id
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|text
__optional__

<.<|
<.<|string

```

```
<.<|fromMe  
__optional__
```

```
<.<|  
<.<|boolean
```

```
<.<|mentions  
__optional__
```

```
<.<|  
<.<|< string > array
```

```
|===  
[[_components_schemas_media-message]]  
==== media-message
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|type  
__optional__
```

```
<.<|  
<.<|enum (image,video,document,ptt,sticker)
```

```
<.<|id  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_message-id>>
```

```
<.<|url  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|caption  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|filename  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|mime  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|fromMe  
__optional__
```

```
<.<|  
<.<|boolean
```

```
|===  
[[_components_schemas_info-message]]  
==== info-message
```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|
<.<|string

<.<|id
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|subtype
__optional__

<.<|
<.<|enum (group/promote,group/demote,group/add,group/remove,group/invite,group/leave)

<.<|participant
__optional__

<.<|
<.<|string

|===

```

```

[[_components_schemas_location-message]]
==== location-message

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: location

<.<|string

<.<|id
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|payload
__optional__

<.<|Format: 'latitude,longitude'

<.<|string

|===
[[_components_schemas_vcard-message]]
==== vcard-message

```

```

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

<.<|Description

<.<|Schema

<.<|type
__optional__

<.<|**Default**: vcard

<.<|string

<.<|id
__optional__

<.<|
<.<|<<_components_schemas_message-id>>

<.<|vcardList
__optional__

<.<|
<.<|< <<_components_schemas_vcard-data>>
> array

|===
[[_components_schemas_multi-vcard-message]]
==== multi-vcard-message

.Properties
[%header,caption=,cols=".^4a,.^16a,.^4a"]
|===
<.<|Name

```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|type  
__optional__
```

```
<.<|**Default**: multi_vcard
```

```
<.<|string
```

```
<.<|id  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_message-id>>
```

```
<.<|vcardList  
__optional__
```

```
<.<|  
<.<|< <<_components_schemas_vcard-data>>  
  > array
```

```
|===  
[[_components_schemas_vcard-data]]  
==== vcard-data
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|displayName  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|vcard  
__optional__
```

```
<.<|  
<.<|string
```

```
|===  
[[_components_schemas_product-data]]  
==== product-data
```

```
.Properties  
[%header,caption=,cols=".^4a,.^16a,.^4a"]  
|===  
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|type  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|productId  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|image  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|url  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|price  
__optional__
```

```
<.<|  
<.<|integer
```

```
<.<|price1000  
__optional__
```

```
<.<|  
<.<|integer
```

```
<.<|title  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|description  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|retailerId  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|business  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|currency  
__optional__
```

```
<.<|  
<.<|string
```

```
<.<|id  
__optional__
```

```
<.<|  
<.<|<<_components_schemas_message-id>>
```

```
|===
```

```
[[_components_parameters]]  
=== Parameters  
.Parameters
```

```
[%header,caption=,cols=".^2a,.^3a,.^10a,.^5a"]
```

```
|===
```

```
<.<|Type
```

```
<.<|Name
```

```
<.<|Description
```

```
<.<|Schema
```

```
<.<|**path**
```

```
<.<|**phone_id** +  
__required__
```

```
<.<|ID of the phone registered to the product, assigned by the database automatically.  
Can be obtained by calling ***GET listPhones***.
```

```
<.<|<<_components_schemas_phone-id>>
```

```
|===
```